

True

FOOD STORAGE

True uses completely sealed, oil-filled, self lubricating, fan motors with a life expectancy of 15-20 years. The motors are matched with the correct size fan blades to optimize the refrigeration performance and allow for faster recovery and better uniform temperature throughout the cabinet.

MADE IN USA



HANDCRAFTED IN AMERICA



For over 70 years, True has been an industry leader in commercial refrigeration and continues to exceed customer's expectations because of our high standards in customer service, quality materials, design, availability and performance.

True Manufacturing is recognized as the leading manufacturer of commercial refrigerators and freezers in the world for the food-service and soft drink industries. The path to that leadership position began in 1945, when Bob Trulaske and his father, Frank, and later his brother, Art, developed a refrigeration company in their house on Lenox Avenue in St. Louis.

From their garage, they built the first 40 cu. ft. upright freezer on the market. Soon after, they began manufacturing Wrapped Rail Roll-Top Bottle Coolers for beer and beverages in a multi-story warehouse on Pine Street in downtown St. Louis, Missouri.

WWW.TRUEMFG.CO
JESSYTRADE.COM

IN THE FOLLOWING PAGES

- SALAD UNIT →
- REFRIGERATOR & FREEZER →
- UNDERCOUNTER →
- DISPLAY CASE →

BROUGHT TO YOU BY
JESSY TRADE



TSSU-27-8

Model	Doors	Shelves	Pans (top)	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
				L**	D†	H*						
TSSU-27-8	1	2	8	27½ 702	30½ 766	36¾ 934	½ ¼	230-240/50/1	4.9 2.9	5-15P ▲	7 2.13	215 98



TSSU-36-8

Model	Doors	Shelves	Pans (top)	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
				L	D†	H*						
TSSU-36-8	2	4	8	36¾ 924	30½ 766	36¾ 934	½ ½	230-240/50/1	8.3 4.2	5-15P ▲	7 2.13	240 109

TSSU-48-8

Model	Doors	Shelves	Pans (top)	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
				L	D†	H*						
TSSU-48-8	2	4	8	48¾ 1229	30½ 766	36¾ 934	½ ½	230-240/50/1	8.6 4.2	5-15P ▲	7 2.13	290 132



TSSU-60-10

Model	Doors	Shelves	Pans (top)	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
				L	D†	H*						
TSSU-60-10	2	4	10	60¾ 1534	30½ 766	36¾ 934	½ ½	230-240/50/1	7.8 4.2	5-15P ▲	7 2.13	320 146

TSSU-72-8

Model	Doors	Shelves	Pans (top)	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
				L	D†	H*						
TSSU-72-8	3	6	8	72¾ 1839	30½ 766	36¾ 934	½ ½	230-240/50/1	10.3 6.7	5-15P ▲	7 2.13	420 191



T-23 Reach-In Solid Swing Door Refrigerator

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D	H*						
T-23	1	3	27 686	29½ 750	78¾ 1991	½ ¼	230-240/50/1	7.6 2.4	5-15P ▲	9 2.74	280 127



T-23F Reach-In Solid Swing Door -10°F Freezer

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D	H*						
T-23F	1	3	27 686	29½ 750	78¾ 1991	½ ½	230-240/50/1	7.2 5.5	5-15P ▲	9 2.74	275 125

T-49 Reach-In Solid Swing Door Refrigerator

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D	H*						
T-49	2	6	54¾ 1375	29½ 750	78¾ 1991	½ ½	230-240/50/1	9.1 5.4	5-15P ▲	9 2.74	420 191



T-49F Reach-In Solid Swing Door -10°F Freezer

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D	H*						
T-49F	2	6	54¾ 1375	29½ 750	78¾ 1991	¾ ¾	230-240/50/1	12.5 4.8	5-20P ▲	9 2.74	510 232

T-72F Reach-In Solid Swing Door -10°F Freezer

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D	H*						
T-72F	3	9	78¾ 1985	29½ 750	79¾ 2010	1 1½	230-240/50/1	12.0 9.0	5-20P ▲	9 2.74	600 273





TUC-27

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H*						
TUC-27	1	2	27 $\frac{3}{8}$ 702	30 $\frac{1}{8}$ 766	29 $\frac{3}{4}$ 756	$\frac{1}{8}$ $\frac{1}{4}$	115/60/1 230-240/50/1	3.9 2.9	5-15P ▲	7 2.13	190 87



TUC-48

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H*						
TUC-48	2	4	48 $\frac{3}{8}$ 1229	30 $\frac{1}{8}$ 766	29 $\frac{3}{4}$ 756	$\frac{1}{8}$ $\frac{1}{8}$	115/60/1 230-240/50/1	5.0 4.2	5-15P ▲	7 2.13	260 118

TUC-48D-4

Model	Drawers	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
		L	D†	H*						
TUC-48D-4	4	48 $\frac{3}{8}$ 1229	30 $\frac{1}{8}$ 766	29 $\frac{3}{4}$ 756	$\frac{1}{8}$ $\frac{1}{8}$	115/60/1 230-240/50/1	5.0 4.2	5-15P ▲	7 2.13	310 141



TUC-60G

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H*						
TUC-60G	2	4	60 $\frac{3}{8}$ 1534	30 $\frac{1}{8}$ 766	29 $\frac{3}{4}$ 756	$\frac{1}{8}$ $\frac{1}{8}$	115/60/1 230-240/50/1	5.1 4.2	5-15P ▲	7 2.13	360 164

TUC-72

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H*						
TUC-72	3	6	72 $\frac{3}{8}$ 1839	30 $\frac{1}{8}$ 766	29 $\frac{3}{4}$ 756	$\frac{1}{8}$ $\frac{1}{2}$	115/60/1 230-240/50/1	8.5 6.7	5-15P ▲	7 2.13	375 171





GDM-10 Glass Door Merchandiser: Swing Door refrigerators with LED lighting.

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H						
GDM-10-LD	1	3	24 3/8 632	23 1/8 588	53 1/2 1359	1/8	115/60/1 230-240/50/1	4.1 4.0	5-15P ▲	9 2.74	200 91

TAC-14GS

Glass Sided Refrigerator Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
		L	D	H						
TAC-14GS	3	30 3/4 769	30 3/8 772	56 3/8 1432	1/8	115/60/1 230-240/50/1	13.9 4.5	5-20P ▲	6.5 1.98	280 127



TAC-48 Vertical Air Curtains

Model	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
		L	D	H						
TAC-48	4	48 1220	30 3/8 766	80 3/8 2048	1	208/230/60 230-240/50/1	12.0 9.0	6-15P ▲	6.5 1.98	540 245

GDM-7

Glass Door Merchandiser:

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H						
GDM-7	1	3	24 610	24 3/8 629	39 3/8 1010	1/8	115/60/1 230-240/50/1	2.5 2.4	5-15P ▲	9 2.74	200 91



GDM-33CPT-54 Glass Door Merchandiser:

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H						
GDM-33CPT-54	2 fr/2 bk	3	39 1/2 1004	24 3/8 613	54 1/2 1375	1/8	115/60/1 230-240/50/1	4.1 5.0	5-15P	9 2.74	360 164

TCGR-36

Curved Glass Refrigerated Bakery Case

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			L	D†	H						
TCGR-36	2	3	36 3/8 937	38 3/8 969	47 7/8 1217	1/8	115/60/1 230-240/50/1	8.8 4.0	5-15P ▲	9 2.74	495 225



THAC-36-S Horizontal Air Curtain Refrigerated Merchandiser

Model	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
		L	D	H						
THAC-36-S	3	36 3/8 918	30 3/8 766	43 3/8 1102	1/8	115/60/1	9.4	5-15P	6.5 1.98	N/A N/A

† Depth does not include 1 1/8" (35 mm) for door handles

▲ Plug type varies by country.